

control guns - metered (hg series)



HG40-01

HG45-01

HG55-01

HG60-01

		automatic shut-off model		automatic shut-off model
Flow range	1-30 L/min	1-30 L/min	1-30 L/min	1-30 L/min
Inlet swivel	½" BSP (F)	½" BSP (F)	½" BSP (F)	½" BSP (F)
Meter	oval gear / mechanical	oval gear / mechanical	oval gear / digital	oval gear / digital
Meter accuracy (Flow rate)	+/- 1% (lube oils)	+/- 1% (lube oils)	+/- 0.5% (lube oils)	+/- 0.5% (lube oils)
Features	4-digit resettable batch totaliser 6-digit accumulative totaliser	pre-settable to 99.9ltrs AUTO shutoff 3-digit resettable batch totaliser 5-digit accumulative totaliser	5-digit resettable batch totaliser 6-digit accumulative totaliser sleep mode to conserve battery life EEPROM information retention for battery change	pre-settable to 1999.9ltrs AUTO Shutoff 5-digit resettable batch totaliser 6-digit accumulative totaliser sleep mode to conserve battery life EEPROM information retention for battery change
Extention	rigid	rigid	rigid	rigid
Non drip nozzle	automatic	automatic	automatic	automatic
Latching trigger	■	■	■	■
Fully serviceable	■	■	■	■
Warranty ¹	10 years	10 years	10 years	10 years
Parts guarantee ²	10 years	10 years	10 years	10 years
Compatible fluids	oils up to SAE140, automatic trans fluid, engine oil, gear oil, hydraulic oil, coolant			
Wetted components	acetal, aluminium, Nitrile rubber, mild steel			
Max working pressure	10 350kPa (1500psi)	10 350kPa (1500psi)	10 350kPa (1500psi)	10 350kPa (1500psi)
Weight (with fittings)	1.16kg	1.16kg	1.16kg	1.16kg

Note¹ Subject to Macnaught warranty terms and conditions, see inside back cover.
 Note² Parts available for 10 years from deletion or upgrade of model.



HGFEX
 250mm (10") flexible extention